

Product Data Sheet

ABC 915 FC POLYURETHANE SEALANT

Product

ABC 915 FC is a high modulus, one component, polyurethane based sealant and adhesive that remains permanently elastic and has good adhesion to most substrates.

Applications

- Facades
- Sealing and bonding metal panels, roofs and trim
- Aluminum, wood and PVC Windows applications.
- Expansion joint sealing in concrete panels, floor joint and road and bridge construction.
- Bonding in container fabrication.

Benefits

- Bonds to concrete, wood, metal, aluminium, polyester, glass, uPVC, stone, ceramics, etc.
- Over paintable with gloss and emulsion paints - preliminary test required before use
- %25 joint movement capacity
- Permanent flexible

Standarts

Product Information

Base	Polyurethane
Packaging	280 ml, 310 ml aluminum cartridges and 600 ml (20 pieces)
Colours	White, Black, Grey, Goldoak, Brown, Beige
Storage and Shelf Life	Store in cool dry conditions between +5°C and 25°C. 12 Months from date of manufacture.

Product Data Sheet

ABC 915 FC POLYURETHANE SEALANT

Technical Properties

Chemical Base	Polyurethane
Curing System	Moisture
Density	1,18 ±0,03 gr/cm ³
Tack Free Time	40 min. (23°C, % 50 R.H)
Curing Time	2mm/24 hours (23 °C , % 50 R.H)
Sagging	0
Elongation at Break	%>350
Tensile Strength	2.0 MPa
Shore A	35-40, DIN 53 505 (N/mm ²)

Product Data Sheet

ABC 915 FC POLYURETHANE SEALANT

Application Details

- All surfaces must be clean, dry and dust free.
- All loose or flaking surface coatings, and old sealant and mastic joints, should be removed before application
- Glass, metal and aluminium should be cleaned with a proprietary solvent cleaner prior to application for optimum adhesion.
- Not for use on substrates that may bleed oils, solvents or plasticisers
- Do not use on bitumen or asphalt.



A Sika BRAND



ABC Kimya Sanayi ve Dış Ticaret A.Ş.

Ortaköy Mah. İlter Bulvarı No: 16
Selimpasa 34582 Silivri / İstanbul / Türkiye

İletişim

Tel: +90 212 422 13 56 (Pbx)
Fax: +90 212 422 13 58
www.abcsealants.com

Product Data Sheet

ABC
Ocak 2017, Versiyon 01.01