

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : OKS 2561

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Corrosion inhibitor

Recommended restrictions on use : Restricted to professional users.

### 1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
82216 Maisach-Gernlinden  
Deutschland  
Tel.: +49 8142 3051 500  
Fax: +49 8142 3051 599  
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com  
National contact :

### 1.4 Emergency telephone number

Emergency telephone number : +49 8142 3051 517 (24/7 service)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561




Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:	  
Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing mist. P273 Avoid release to the environment. <b>Storage:</b> P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

butanone

acetone

n-butyl acetate

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version  
1.0

Revision Date:  
16.09.2024

Date of last issue: -  
Date of first issue: 16.09.2024

Print Date:  
17.09.2024

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.  
Metal powder

#### Components

Chemical name	CAS-No. EC-No.  Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
butanone	78-93-3 201-159-0  606-002-00-3	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 30 - < 50
acetone	67-64-1 200-662-2  606-001-00-8	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		>= 10 - < 20
cyclopentanone	120-92-3 204-435-9  606-025-00-9	Flam. Liq.3; H226 Skin Irrit.2; H315 Eye Irrit.2; H319		>= 1 - < 10
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3  030-001-01-9	Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 1/1	>= 2.5 - < 10
n-butyl acetate	123-86-4 204-658-1  607-025-00-1	Flam. Liq.3; H226 STOT SE3; H336; EUH066		>= 1 - < 10
Substances with a workplace exposure limit :				
dimethyl ether	115-10-6	Flam. Gas1A;		>= 30 - < 50

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version 1.0      Revision Date: 16.09.2024      Date of last issue: -      Print Date: 17.09.2024  
Date of first issue: 16.09.2024

	204-065-8 603-019-00-8	H220 Press. GasLiquefied gas; H280	Note U (table 3.1)	
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1	Flam. Sol.1; H228	Note T	$\geq 1 - < 10$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
Seek medical advice.
- If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema

Risks : Central nervous system depression  
Can be absorbed through skin.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : ABC powder  
Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides  
Halogenated compounds  
Metal oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Refer to protective measures listed in sections 7 and 8.  
Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Non-sparking tools should be used.

#### 6.4 Reference to other sections

For personal protection see section 8.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

### 7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butanone	78-93-3	TWA	200 ppm 600 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	300 ppm 899 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	300 ppm 900 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
		Further information: Indicative		
		TWA	200 ppm 600 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
		Further information: Indicative		
dimethyl ether	115-10-6	TWA	400 ppm 766 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		STEL	500 ppm	GB EH40

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version  
1.0

Revision Date:  
16.09.2024

Date of last issue: -  
Date of first issue: 16.09.2024

Print Date:  
17.09.2024

			958 mg/m <sup>3</sup>	(2005-04-06)
		TWA	1,000 ppm 1,920 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
	Further information: Indicative			
acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		STEL	1,500 ppm 3,620 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		TWA	500 ppm 1,210 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
	Further information: Indicative			
aluminium powder (stabilised)	7429-90-5	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40 (2011-12-01)
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40 (2011-12-01)
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U (2019-10-31)
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U (2019-10-31)
	Further information: Indicative			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
butanone	78-93-3	butan-2-one: 70 micromol per litre (Urine)	After shift	GB EH40 BAT (2011-12-18)

### Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
dimethyl ether acetone	Workers	Inhalation	Long-term exposure effects	1894 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1210 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	186 mg/kg
cyclopentanone	Workers	Inhalation	Long-term systemic effects	61 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	7 mg/kg

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version  
1.0

Revision Date:  
16.09.2024

Date of last issue: -  
Date of first issue: 16.09.2024

Print Date:  
17.09.2024

			effects	
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	83 mg/kg
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Dermal	Long-term local effects	11 mg/cm <sup>2</sup>

### Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
dimethyl ether	Fresh water	0.155 mg/l
	Marine water	0.016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0.681 mg/kg
	Marine sediment	0.069 mg/kg
	Soil	0.045 mg/kg
acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine sediment	3.04 mg/kg
	Soil	29.5 mg/kg
zinc powder — zinc dust (stabilised)	Fresh water	0.0206 mg/l
	Fresh water sediment	117.8 mg/kg
	Marine water	0.0061 mg/l
	Marine sediment	56.5 mg/kg
	Microbiological Activity in Sewage Treatment Systems	0.052 mg/l
	Soil	35.6 mg/kg
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Microbiological Activity in Sewage Treatment Systems	35.6 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine sediment	0.0981 mg/kg
	Soil	0.09 mg/kg

## 8.2 Exposure controls

### Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields
- Hand protection
- Material : Nitrile rubber
  - Break through time : > 10 min
  - Protective index : Class 1
- Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Recommended Filter type:  
Organic gas and low boiling vapour type (AX)
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : aerosol
- Colour : silver
- Odour : characteristic
- Odour Threshold : No data available
- pH : Not applicable  
substance/mixture is non-soluble (in water)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : -60 °C  
Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 15 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Vapour pressure : 5,500 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0.69 (20 °C)  
Reference substance: Water  
The value is calculated

Density : 0.69 g/cm<sup>3</sup>  
(20 °C)

Bulk density : No data available

Solubility(ies)  
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : 365 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

### 9.2 Other information

Sublimation point : No data available  
Self-ignition : No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazards to be specially mentioned.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.  
Risk of receptacle bursting.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:  
Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.  
Harmful by inhalation.  
Symptoms: Inhalation may provoke the following symptoms:;  
Respiratory disorder, Dizziness, Drowsiness, Vomiting,  
Fatigue, Vertigo, Central nervous system depression

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

Symptoms: Skin disorders

### Components:

#### **butanone:**

Acute oral toxicity : LD50 (Rat): 2,193 mg/kg  
Method: OECD Test Guideline 423  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

#### **acetone:**

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

#### **cyclopentanone:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

#### **zinc powder — zinc dust (stabilised):**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.41 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity

#### **n-butyl acetate:**

Acute oral toxicity : LD50 (Rat): 10,768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l  
Exposure time: 4 h

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute  
inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17,600 mg/kg

### dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 309 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

### aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute  
inhalation toxicity

## Skin corrosion/irritation

### Product:

Remarks : This information is not available.

### Components:

#### butanone:

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

#### cyclopentanone:

Species : Rabbit  
Result : Skin irritation

#### zinc powder — zinc dust (stabilised):

Species : Rabbit  
Assessment : No skin irritation  
Result : No skin irritation

#### n-butyl acetate:

Species : Rabbit

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : Repeated exposure may cause skin dryness or cracking.

### dimethyl ether:

Assessment : No skin irritation  
Result : No skin irritation

### aluminium powder (stabilised):

Species : Rabbit  
Assessment : No skin irritation  
Result : No skin irritation

### Serious eye damage/eye irritation

#### Product:

Remarks : Irritating to eyes.

#### Components:

##### butanone:

Species : Rabbit  
Assessment : Irritating to eyes.  
Method : OECD Test Guideline 405  
Result : Irritating to eyes.

##### acetone:

Species : Rabbit  
Result : Eye irritation

##### cyclopentanone:

Species : Rabbit  
Result : Eye irritation

##### zinc powder — zinc dust (stabilised):

Species : Rabbit  
Exposure time : 24 h  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

##### n-butyl acetate:

Species : Rabbit  
Assessment : No eye irritation

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### dimethyl ether:

Assessment : No eye irritation  
Result : No eye irritation

### aluminium powder (stabilised):

Species : Rabbit  
Assessment : No eye irritation  
Result : No eye irritation

### Respiratory or skin sensitisation

#### Product:

Remarks : This information is not available.

#### Components:

##### butanone:

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

##### zinc powder — zinc dust (stabilised):

Species : Guinea pig  
Assessment : Did not cause sensitisation on laboratory animals.  
Method : OECD Test Guideline 406  
Result : Did not cause sensitisation on laboratory animals.  
GLP : yes

##### n-butyl acetate:

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

##### dimethyl ether:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Assessment : Does not cause skin sensitisation.  
Result : Does not cause skin sensitisation.

### aluminium powder (stabilised):

Species : Guinea pig  
Assessment : Did not cause sensitisation on laboratory animals.  
Result : Did not cause sensitisation on laboratory animals.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available  
Genotoxicity in vivo : Remarks: No data available

#### Components:

##### butanone:

Germ cell mutagenicity-  
Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

##### zinc powder — zinc dust (stabilised):

Germ cell mutagenicity-  
Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

##### n-butyl acetate:

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Method: OECD Test Guideline 471  
Result: negative  
  
Test Type: Chromosome aberration test in vitro  
Test system: Chinese hamster cells  
Method: OECD Test Guideline 473  
Result: negative  
  
Genotoxicity in vivo : Species: Mouse  
Application Route: Oral  
Method: OECD Test Guideline 474  
Result: negative  
  
Germ cell mutagenicity-  
Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

##### dimethyl ether:

Genotoxicity in vitro : Test Type: Ames test



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction  
- Teratogenicity -  
No effects on or via lactation

### zinc powder — zinc dust (stabilised):

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction  
- Teratogenicity -  
No effects on or via lactation

### n-butyl acetate:

Effects on fertility : Test Type: Two-generation study  
Species: Rat  
Application Route: inhalation (vapour)  
General Toxicity - Parent: NOAEC: 750 mg/l  
General Toxicity F1: NOAEC: 750 mg/l  
General Toxicity F2: NOAEC: 750 mg/l  
Method: OECD Test Guideline 416  
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Reproductive toxicity - Assessment : - Fertility -  
No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.  
- Teratogenicity -  
No toxicity to reproduction

### dimethyl ether:

Reproductive toxicity - Assessment : - Fertility -  
Animal testing did not show any effects on fertility.

### STOT - single exposure

#### Product:

Remarks : No data available

#### Components:

##### butanone:

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.,

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

May cause drowsiness or dizziness.

### **acetone:**

Exposure routes : Inhalation  
Assessment : May cause drowsiness or dizziness.

### **n-butyl acetate:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### **STOT - repeated exposure**

#### **Product:**

Remarks : No data available

#### **Components:**

##### **butanone:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### **n-butyl acetate:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### **Repeated dose toxicity**

#### **Product:**

Remarks : This information is not available.

#### **Components:**

##### **n-butyl acetate:**

Species : Rat  
NOAEL : 125 mg/kg  
Application Route : Oral

### **Aspiration toxicity**

#### **Product:**

This information is not available.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

### Components:

#### **butanone:**

No aspiration toxicity classification

#### **zinc powder — zinc dust (stabilised):**

No aspiration toxicity classification

#### **n-butyl acetate:**

No aspiration toxicity classification

#### **dimethyl ether:**

No aspiration toxicity classification

### **Further information**

#### Product:

Remarks : Risks of irreversible effects after a single exposure.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

### 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation : Remarks: No data available

### 12.4 Mobility in soil

**Product:**

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : Toxic to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied  
16 05 04\*\*, gases in pressure containers (including halons)  
containing hazardous substances

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1950  
RID : UN 1950  
IMDG : UN 1950  
IATA : UN 1950

### 14.2 UN proper shipping name

ADR : AEROSOLS  
RID : AEROSOLS  
IMDG : AEROSOLS  
IATA : Aerosols, flammable

### 14.3 Transport hazard class(es)

ADR : 2  
RID : 2  
IMDG : 2.1  
IATA : 2.1

### 14.4 Packing group

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation (UK SVHC) : This product does not contain substances of very high concern (UK: The REACH etc. (Amendment) Regulations, Article 57).

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

Britain)  
(GB POPs)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : acetone

UK REACH List of substances subject to authorisation (Annex XIV) (UK. REACH Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation (GB PIC) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) P3a FLAMMABLE AEROSOLS  
E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 84.18 %

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

## 15.2 Chemical safety assessment

This information is not available.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

### SECTION 16: Other information

#### Full text of R-Phrases

- Note T : This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
- Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

#### Full text of H-Statements

- EUH066 : Repeated exposure may cause skin dryness or cracking.
- H220 : Extremely flammable gas.
- H225 : Highly flammable liquid and vapour.
- H226 : Flammable liquid and vapour.
- H228 : Flammable solid.
- H280 : Contains gas under pressure; may explode if heated.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.
- H336 : May cause drowsiness or dizziness.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

- Note T : This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

- hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
- Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- 2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
- GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
- GB EH40 BAT : UK. Biological monitoring guidance values
- 2000/39/EC / TWA : Limit Value - eight hours
- 2000/39/EC / STEL : Short term exposure limit
- 2019/1831/EU / TWA : Limit Value - eight hours
- 2019/1831/EU / STEL : Short term exposure limit
- GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
- GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



## OKS 2561

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	16.09.2024	Date of first issue: 16.09.2024	17.09.2024

concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 2	H411

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.